

High Back Rocking Chair Assembly Instructions



Tools:

Square Drive Tip (included) with a Power Screwdriver (not included). ½" Socket and Ratchet.

Parts Included:

- A Left Side Assembly (1)
- B Right Side Assembly (1)
- C Back Assembly (1)
- D Front Seat Rail (1)
- E Under Seat Supports (1)
- F Seat Slats (5)
- G 3" Colored Screws (8)
- H 2.5" Colored Screws (1)
- I 2" Uncolored Screws (5)
- J Colored 1½" Screws (7)
- K Square Drive Tip for Power Screwdriver
- L 4" Hex Head Lags (4)
- M Rocker (2)
- N Washers (4)

Instructions:

1. Place Left Side Assembly (A) laying on flat surface with mortise holes sticking up.
2. Place Back Assembly (C) in mortise holes in left side assembly.
3. Place Front Seat Rail (D) in mortise hole in Left Side Assembly.
4. Place Seat Slats (F) in mortise holes in Left Side Assembly.

5. Line up Seat Slats, Back Assembly and Front Seat Rail. Place Right Side Assembly (B) on top, making sure Slats fit into notches on Right Side Assembly.
6. Locate pilot holes and attach Right Side Assembly to Back Assembly using 3" screws (G).
7. Locate Pilot holes and attach Right Side Assembly to Front Seat Rail using 3" screws.
8. Locate Pilot holes and attach the Middle and Outer Slats to the Right Side Assembly using 1½" Screws (J).
9. Flip Chair over with Left Side up. Locate Pilot holes and attach the Middle and Outer Slats to the Left Side Assembly using 1½" Screws.
10. Locate Under Seat Support (E). Place Tenon in hole in Front Seat Rail and slide into groove in Back Assembly.
11. Attach Under Seat Support to Front Seat Rail with 1¾" screw (J). Attach Under Seat Support to Back Assembly using 2.5" Screw (H).
12. Flip Chair so that the under seat is accessible. Locate Pilot holes and attach Under Seat Support to Seat Slats using 2" Screws (I).
13. Lay chair on side and attach Rocker Leg (M) to End Assembly using Lag Bolts (L) with Washer (N). Tighten using ½" socket and ratchet. Repeat for other leg.